

# PS-3410 TH TLC

## High torque chain saw for arborists

Designed for professional tree care operations and for use from lift buckets for maintenance, crown cleanup, trimming and dead wood removal.



### Technical specifications

Displacement	34 cm <sup>3</sup>	Automatic oilpump	yes
Power rating	1,4 kW	Sound pressure level	94,1 dB(A)
Power rating	1,9 PS	Sound power level	102,9 dB(A)
Weight (dry, w/o bar)	3,6 kg	Uncertainty K according to 2006/42/EC	2,5 dB(A)
Fuel tank capacity	0,28 l	Vibration acceleration Front	4,7 m/s <sup>2</sup>
Oil tank capacity	0,22 l	Vibration acceleration Rear	5,2 m/s <sup>2</sup>
Vibration damping	yes	Uncertainty K according to 2006/42/EC	2,0 m/s <sup>2</sup>
Chain tensioning	Toolless Chain tensioning (TLC)		

- **Not available for sale into California**
- High torque 34 cm<sup>3</sup> engine
- Effective vibration damping
- Good starting in every position, easystart optimized
- Low kickback saw chain for safe working
- Automatic oil pump for reliable chain lubrication
- Tank cap easy operatable by hand or by combination wrench
- Tool less chain tensioning

DOLMAR GmbH .

A Member of the Makita Group

[www.dolmar.com](http://www.dolmar.com)

