

ES-2140 AP


Powerful and reliable



5 m cable as a standard



Tool-less chain tensioner (TLC)



Metal spike bar



Soft handle and big trigger switch provide safety and comfort

Technical specifications

Rated voltage	230 V	Chain	092 3/8"
Power consumption	2.000 W	Sound pressure level	90,8 dB(A)
Weight (dry, w/o bar)	5,2 kg	Sound power level	101,8 dB(A)
Oil tank capacity	140 ml	Uncertainty K according to 2006/42/EC	1,0 dB(A)
Chain tensioning	Toolless Chain tensioning (TLC)	Vibration acceleration Front	4,7 m/s ²
Automatic oilpump	yes	Vibration acceleration Rear	5,6 m/s ²
Guide bar	40 cm	Uncertainty K according to 2006/42/EC	1,5 m/s ²

- Powerful and extremely heavy-duty Makita electric motor
- Ergonomic hand guard with non-slip coating
- Automatic oil pump for reliable chain lubrication
- Toolless chain tensioner
- Metal spike bar for effective force deflection
- Oil fill level window
- Electric runout brake
- Electric overload protection
- Professional bar
- With 5m cable
- Initial current limiter

DOLMAR GmbH

A Member of the Makita Group

www.dolmar.com

