

RM-72.13 H

Fits through every garden gate



Adjustable comfort seat



Water connector for easy deck cleaning



Hydrostatic gear box - no gear changing



Grasfangkorbentleerung durch Handbetätigung

Technical specifications

Engine manufacturer	Briggs & Stratton	Gear type	Hydrostatic
Engine type	Powerbuilt 3130 AVS	Cutting tool clutch	Mechanical
Displacement	344 cm ³	Deck	Single Blade
Power rating at 2800 rpm	6,8 kW	Dimensions	186 x 76 x 110 cm
Engine Vibration Damping	AVS	Sound pressure level	85,2 dB(A)
For lawn surface up to approx.	3.000 m ²	Uncertainty K according to 2006/42/EC	0,6 dB(A)
Width	71 cm	Sound power level	99,1 dB(A)
Cutting height (min)	30 mm	Uncertainty K according to 2006/42/EC	0,4 dB(A)
Cutting height (max)	75 mm	Vibration acceleration (Seat)	0,70 m/s ²
Container capacity	170 l	Uncertainty K according to 2006/42/EC	0,3 m/s ²
Weight	168 kg		

- Hydrostatic gear box - no gear change
- E-start for easy engine starting
- Reliable Briggs & Stratton engine
- Heavy duty single blade steel deck
- Water connector for easy deck cleaning
- Large grass box, discharge from driver's seat
- Acoustic signal for grass box full
- Battery charger included

DOLMAR GmbH

A Member of the Makita Group

www.dolmar.com

DOLMAR