

# PS-222 TH

## Lightweight top handle chain saw

Designed for professional tree care operations and for use from lift buckets for maintenance, crown cleanup, trimming and dead wood removal.



Technical specifications			
Displacement	22,2 cm <sup>3</sup>	Automatic oilpump	yes
Power rating	0,74 kW	Sound pressure level	95,0 dB(A)
Power rating	1,02 PS	Sound power level	104,1 dB(A)
Weight (dry, w/o bar)	2,5 kg	Uncertainty K according to 2006/42/EC	2,5 dB(A)
Fuel tank capacity	0,2 l	Vibration acceleration Front	6,0 m/s <sup>2</sup>
Oil tank capacity	0,19 l	Vibration acceleration Rear	5,0 m/s <sup>2</sup>
Vibration damping	yes	Uncertainty K according to 2006/42/EC	2,0 m/s <sup>2</sup>
Chain tensioning	Lateral tensioning		

- 2,5 kg only!
- 22,2-cm<sup>3</sup>-Engine - powerful for making full use of a 25cm guide bar
- EasyStart with automatic half-throttle lock, primer pump and spring supported starter
- Automatic oil pump for reliable chain lubrication
- Low kickback saw chain for safe working

DOLMAR GmbH .

A Member of the Makita Group

[www.dolmar.com](http://www.dolmar.com)

