

PC-6412 D

For concrete, asphalt and steel



Hood adjsuht with integrated notch



Centrally mounted cutting disc



Laterally mounted cutting disc



Easy belt tensioning with screw driver

Technical specifications

Engine	2-stroke	Wheel Ø	300 mm
Displacement	64 cm ³	Arbor Ø	20 mm
Power rating	3,3 kW	Sound pressure level	99,5 dB(A)
Power rating	4,5 PS	Sound power level	108,9 dB(A)
Fuel tank capacity	1,1 l	Uncertainty K according to 2006/42/EC	2,5 dB(A)
Circumferential speed	80 m/s	Vibration acceleration Front	5,7 m/s ²
Weight (without blade, fuel, oil)	9,7 kg	Vibration acceleration Rear	5,1 m/s ²
Max cutting depth	97 mm	Uncertainty K according to 2006/42/EC	2,0 m/s ²

- Large foam filter
- Paper filter with longitudinal gills
- Vibration-Proof cover hood fastening
- Easy operating with one lever switch
- Automatic gas level at cold start / choke position
- Head decompression valve with rubber cover for heat protection
- Optimum cooling air flow for good conditions under heavy duty service
- All rpm extended compensator function - corrects fuel amount with increasing air filter contamination

DOLMAR GmbH

A Member of the Makita Group

www.dolmar.com

DOLMAR