

# PS-4605

**Powerful, agile and reliable**

The formula for the professional DOLMAR mid-range model, with high torque for felling and stripping of mid-sized trees, but also ideal for de-branching operations because of its ergonomic design, high RPM and racy acceleration.




Thanks to smooth surfaces, the models are easy to handle and clean



The advantageous chain space is easy to clean and lets the chips fly where they may



Optimum chip exhaust for avoiding jams



Lateral chain tensioning

Technical specifications			
Displacement	45,6 cm <sup>3</sup>	Automatic oilpump	yes
Power rating	2,6 kW	Handle Heating	no
Power rating	3,5 PS	Sound pressure level	101,2 dB(A)
Weight (dry, w/o bar)	5,3 kg	Sound power level	109,1 dB(A)
Fuel tank capacity	0,47 l	Uncertainty K according to 2006/42/EC	2,5 dB(A)
Oil tank capacity	0,27 l	Vibration acceleration Front	4,1 m/s <sup>2</sup>
Vibration damping	yes	Vibration acceleration Rear	3,6 m/s <sup>2</sup>
Chain tensioning	Lateral tensioning	Uncertainty K according to 2006/42/EC	2,0 m/s <sup>2</sup>

- Easy Start: Spring assisted starter combined with optimized engine management significantly reduces resistance
- MPI technology (Memory-Power-Ignition) for easy restart
- Powerful engine for felling and chopping medium-thick wood
- Good cooling for a high reliability
- High rpm and super-fast acceleration
- Ergonomic design, easy handling
- Touch&Stop one lever service for immediate shut-off
- Tool-less filter maintenance
- Lateral chain tensioning provides easy operator access
- Optimum chip flow through
- Adjustable oil pump, disabled at engine idling

DOLMAR GmbH .

A Member of the Makita Group

[www.dolmar.com](http://www.dolmar.com)

